



LEADER 4

British designed and
built for British farmers



Shown with 4000L tank and 24m boom



Leader 4

team-sprayers.com • 01353 661 211

STANDARD FEATURES

Controls



Muller Track Guide 3 ISOBUS terminal with area mapping, field guidance and GPS 12 section boom control
Supplied as standard with an EGNOS A101 receiver and Multi function grip to control all spray & hydraulic functions.



Hydraulic and spray valves are mounted at the rear and protected by a moulded cover.

Boom re-circulation: system with ARAG air-stop nozzle assemblies (air supply taken from tractor).



Work station controlling primary functions to operate the sprayer and when cleaning or filling.



Chemical induction: 25L stainless steel hopper for safe transfer of liquids and powders via a high pressure venturi system to the main tank, a rotary nozzle for cleaning containers.



Bertolini diaphragm pump: High quality Poly' series to withstand any aggressive plant protection chemicals.



PPE storage: Clothing and PPE lockers.



Clean water supply for tank, spray line and system rinsing (400L).



Axle air suspension absorbs the shock loads instead of transferring them to the main chassis or boom.

Booms



Boom construction:

All booms are manufactured from steel tubular sections. The three dimensional structure guarantees strength and durability.

All nozzles and spray lines are secured above the base of the boom for protection against accidental damage.



Boom adjustment:

All pivot points and fold rams can be adjusted to counteract wear.

Pantograph boom lift system ensures excellent stability and performance, damped by a nitrogen accumulator. Boom adjustment height from 500 to 2500mm.



Boom stowage system: Secures boom assembly in the folded position for safe road transport.



'Break back' boom design is a standard feature on all models to avoid damage from unseen obstructions.



Boom flexibility: it is possible to work with the boom part-folded:

2 fold	3 fold
18 to 9m	28 to 12m
20 to 11m	30 to 12m
21 to 11m	32 to 12m
24 to 12m	




Tracking/steering axle ensures the wheels of the sprayer follow in the 'wheelings' of the tractor to minimise crop damage. Manual / automatic field modes.

OPTIONAL EXTRAS



Fast fill pump hydraulically driven 2" 700L/min pump for main tank fill or tank pump out.

Retractable hose reel and lance kit for cleaning down



Other Standard Fittings

- Hydraulic boom tilt
- Road lighting & brakes
- Dry tank level sight gauge
- Spray boom in-line filters
- Triple nozzles

Other Optional Extras

- GPS boom section switching and mapping
- Stainless steel spray lines
- Bout/foam maker
- One-side boom fold *(outer section only)*



Leader 4

TECHNICAL SPECIFICATIONS


Item	Dimension
Tank capacities [L]	3000, 4000
Pumps [type / L per min]	Poly 2180 /180; Poly 2250 / 250
Boom lengths [m]	18, 20, 21, 24, 28, 30, 32, 36
Hydraulic outlet required	one double acting
Weight - draw bar, empty [kg]	840
Weight - axle, empty [kg]	2720
Weight - total*, empty [kg]	3560
Turning radius [m]	7.00
Total height [m]	3.30 [with boom folded]
Width up to 24m	2.70m
Width 28 - 30m	3.1m
Length draw bar to axle [m]	4.30 Steering draw bar
Clearance 12.4 x 46 wheels [m]	0.76
Rinse tank [L]	300 or 400

Notes: The Leader 4 is available with a range of booms from 18 to 36m [28, 30, 32 and 36m are tri-fold].

All booms have pendulum suspension and anti-yaw damping. The Leader 4 chassis and boom have been designed to meet the rigorous demands of any farming environment.

We reserve the right to improve machine specification without prior notice.

*Weight shown for 3000 litre tank with 24m boom.



4000L with 24m boom and standard drawbar



— ESTABLISHED 1981 —

Leaders in the field of application

Team Sprayers Ltd
Unit 3 Lancaster Way Business Park,
Witchford, Ely, Cambridgeshire CB6 3NW

E sales@team-sprayers.com 

team-sprayers.com • 01353 661211